

HIGHGROVE L SHAPE BATH USER GUIDE

IMPORTANT USERS INSTRUCTIONS

**PLEASE READ CAREFULLY AND RETAIN FOR FURTHER USE.
IMPROPER USE OR CARE CAN INVALIDATE THE WARRANTY.**

OPERATING INSTRUCTIONS

The bath features an inward opening door for easy access. A latch lock is located on the door opening side and locks into position by 'slam shutting' as any domestic door. A 'pull up' knob on adjoining rim releases lock to open. Always leave the door open when not in use to prevent wear of the seal.

The bath must only be filled and emptied of water when the door is in the locked position. The bath is supplied with a single plug & chain waste or with a pop-up option. When a pop-up is supplied turn anti-clockwise to close waste and clockwise to open.

- 1) Close the waste and enter bath.
- 2) 'Slam shut' door to lock into position. Pull on door to check it is locked and push outwards towards lock if required.
BATH IS NOW READY FOR FILLING
- 3) After bathing turn levers on pop-ups to drain the water and remain seated whilst bath is draining.
- 4) When bath has drained pull door knob upwards to release and open door.
- 5) Exit bath. **Leave the door unlocked** to ensure seal is not permanently compressed.

FILL BATH ONLY WHEN OCCUPIED AND DOOR SHUT

** NEVER ATTEMPT TO OPEN DOOR WHEN BATH IS FILLED WITH WATER **

** DO NOT LEAN ON DOOR OR USE FOR SUPPORT **

** ALWAYS LEAVE THE DOOR OPEN WHEN NOT IN USE TO PRESERVE THE SEAL**

CARE AND MAINTENANCE

The Bath is manufactured to a very high standard in G.R.P. (Reinforced Plastic) to ensure its durability and appearance is maintained over many years of use. It has a robust, smooth and warm surface which is non-porous, resistant to dirt and bacteria and easy to clean and maintain.

This bath will give many years of service and continue to look good if cleaned correctly and treated with care.

CLEANING

1. As with standard baths cleaning is subject to scale buildup, which depends on the water hardness. In soft water areas, wash down with warm water and any standard bath detergent applied with a soft cloth or sponge. In hard water areas, non-abrasive or mild acid cleansers can be used. Clean regularly followed by wiping with a dry soft cloth.

Widely available proprietary plastic/enamel bath cleansers are ideal cleaning agents that offer the advantage of a polished shine without rubbing down.

For the extra sparkle, and to further preserve the surface, the Bath can be gently polished occasionally. Beeswax and Brasso (Brass Polish) are suitable for this purpose. Polishing the anti-slip base should be treated with caution so as not to diminish its effectiveness.

2. The stainless steel lock receiver on door and lock cover plate can be polished occasionally with a stainless steel polish to ensure it does not discolour. It is recommended the latch lock is lubricated on average once a year subject to the chlorine content in the water. A lubricant such as “WD 40” or ‘Mr Sheen General Aerosol Polisher’ would be ideal.
3. The white silicone seal along bath door sides should be cleaned occasionally. Use detergent and warm water applied with a sponge or soft cloth. Apply gently and refrain from excessive rubbing.
4. Ideally all chrome or gold plated furniture should be wiped down dry after use. Clean with soapy water and buff with a dry soft cloth only. Note: Surfaces can easily be damaged with acid/abrasive cleaners or with a rough cloth/sponge.

CAUTION

- **DO NOT LOCK THE DOOR WHEN BATH IS NOT IN USE AS THIS WILL WEAR OUT THE SEAL .**
- **KEEP THE WHITE SILICONE SEAL FREE OF ANY BUILD UP OF DEPOSITS. CLEAN GENTLY AND AVOID UNNECESSARY HANDLING.**
- **DO NOT APPLY ANY UNDUE FORCE TO THE BATH DOOR. HANDLE GENTLY.**



SPECIAL NEEDS BATH LTD
37 WARREN STREET
LONDON W1 5PD
13
EN14516 – CL2